

## *Comparativa U1602A y U1604A*

	<b>U1602A</b>	<b>U1604A</b>
<b>Channel Count</b>	2	2
<b>Bandwidth</b>	20 MHz	40 MHz
<b>Waveform Display</b>	Color	Color
<b>Maximum Real Time Sample Rate</b>	200 MSa/s	200 MSa/s
<b>Channel Memory Depth</b>	125,000 Points	125,000 Points
<b>FFT Function</b>	Not Available	Available
<b>Zoom Function</b>	Available	Available
<b>Dual Waveform Math Functions</b>	Available	Available
<b>Multimeter Function</b>	Available	Available
<b>Data Logger Function</b>	Available	Available
<b>IO Interface</b> (standard)	USB 2.0 Full speed	USB 2.0 Full speed
<b>Optional I/O Interface</b>	USB Host	USB Host
<b>Operating temperature</b>	0° C to +50° C	0° C to +50° C
<b>Safety Compliance</b>	Cat III 300 V	Cat III 300 V
<b>Battery</b>	NiMH Rechargeable with power adapter	NiMH Rechargeable with power adapter
<b>Dimensions (mm)</b>	241 x 138 x 66	241 x 138 x 66
<b>Approximate Weight (kg)</b>	1.5	1.5